

### MPR-Threaded plates galvanised

#### Field of application


- For fixing of attachment parts in the rail slot of the MPR-Support channels
- For indoor use

#### Advantages

- Interlocking threaded plate for secure positive connection in the rail slot of the MPR-Support channels
- Galvanised version for use in dry interiors



For support channels	Thread	Part no.	Sales unit	Pack unit	Dimensions [mm]		
					l	b	s
41/21/2.0, 41/41/2.0, 41/41/2.5, 41/62/2.5, 41/42/2.0, 41/82/2.0, 41/124/2.5	M6	<b>151051</b>	100	pieces	34.5	19.5	6.0
	M8	<b>151052</b>					8.0
41/21/2.0, 41/41/2.0, 41/41/2.5, 41/62/2.5, 41/82/2.0, 41/124/2.5	M10	<b>151053</b>	25				9.0
	M12	<b>151054</b>					10.0
41/41/2.0, 41/41/2.5, 41/62/2.5, 41/82/2.0, 41/124/2.5	M16	<b>151055</b>				30.5	



For support channels Material thickness [mm]	Thread	MPR-Threaded plates Tensile load Fz with threaded pin 4.6 and washer 40 x 3 mm [N]	For a tightening torque of [Nm]
2.0	M6	2.400	4
	M8	4.500	9
	M10		17
	M12		29
	M16		
2.5	M6	2.400	4
	M8	4.500	9
	M10	5.000	17
	M12		29
	M16		